

www.koolance.com

## **Specifications Sheet**

Generated: 2025-08-21

## P/N: PC5-1336SL

## PC5-1336SL Liquid Cooling System, Silver [no nozzles or pump]





The PC5-1300 series offers heat dissipation of up to 1300W using a Koolance pre-installed quad-120mm fan heat exchanger. There is no pump included with this system, allowing you to choose among Koolance's <u>RP-1000</u>, <u>PMP-450</u>, <u>PMP-400</u>, or anything else! (Note: The RP-1000 is the reservoir, pump, and electronic control unit used in the Koolance PC4-1000 series system.)

The PC5-1300 1.3kW series is for heavy thermal applications with multiple heat sources: multi-CPU, video cards, and other components which can benefit from high heat capacity liquid cooling.

- · Easy-latch side door
- Three interior zones to isolate hardware for better heat dissipation
- Front and rear case perforations for improved ambient conditions
- Sliding hard drive tracks for easy installation
- · Aluminum rolling casters with brake
- Front USB 2.0 and 1394 Firewire ports
- Includes front and rear 120mm case fans

NOTE: PC5-1326 and PC5-1236 systems will fit power supplies deeper than 9.5" (24.1cm) if the nearest hard drive bay is removed. This would reduce the 3.5" hard drive capacity by half.

| General             |                     |
|---------------------|---------------------|
| Weight              | 38.95 lb (17.67 kg) |
| Cooling Systems     |                     |
| Display Type        | LED                 |
| Fans                | 4 x 120mm (360CFM)  |
| Power Source        | 12 VDC              |
| Radiator            | Aluminum            |
| Temperature Sensors | 50K Thermistors     |