


**QD4 Female Quick Disconnect No-Spill
Coupling, Compression for 13mm x 19mm
(1/2in x 3/4in) *Black***




Koolance patented quick disconnect no-spill coupling with automatic shutoff. 13mm (1/2in) ID, 19mm (3/4in) OD female straight connection with compression fitting. It will only fit a Koolance QD4 male quick disconnect.

After pulling the ring on the female QDC side, the quick-disconnect fittings will separate. Liquid on both sides will be automatically obstructed with approximately 0.2ml freed. Coolant volume lost upon disconnection will rise with internal pressure higher than 0.5kgf/cm² (7psi).

General	
Weight	0.36 lb (0.16 kg)
Max No-Spill Pressure	0.5kgf/cm ² (7psi)
Max Pressure Tolerance @ 25°C	8kgf/cm ² (113.8psi)
Max Temperature Tolerance	80°C (176°F)
Min Pressure Tolerance @ 25°C	-1.0kgf/cm ² (-14psi)
Min Storage Temperature (*No Freezing)	-20°C (-4°F)
Seal Material	EPDM (Water/Glycol Liquids)
Wetted Materials	Brass, Stainless Steel, EPDM





REV	DATE	CONTENTS	REVD BY	CHKD BY	APPD BY
REVISION					

NO.		DISCRIPTION			MATER'L		QUANTITY	REMARKS	
		DECIMAL PLACES	INCHES	MILLIMETRES	UNIT	MM	ITEM	QD4	
		.XXX .XX .X	±.005 ±.010 ±.020	±0.1 ±0.3 ±0.5	SCALE	N/S	TITLE	QD4-FS13X19 QD4-FS13X19-BK	
		ANGULAR DIMENSIONS			3RD ANGLE		CODE NO.	DWG. NO.	PAGE
DATE	BY	BY	BY	APPRO BY	XX° XX.X°		±0.5° ±0.1°		
	SONG				SURFACE ROUGHNESS		SURFACE .63		
							SURFACE 1.6		